SAFETY DATA SHEET



1. Identification

Product identifier BEHR® ULTRA Stain-Blocking Flat Ceiling Paint & Primer - Ultra Pure White

Other means of identification

Product code 5558

Recommended use **Architectural Coating**

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process LLC

> 1801 E. St. Andrew Place Santa Ana. CA 92705

714-545-7101 **Telephone** +1 760 476 3962 **Emergency telephone**

+1 866 519 4752

335213 Access code

2. Hazard(s) identification

Physical hazards Not classified. Not classified. **Health hazards OSHA** defined hazards Not classified.

Label elements

Hazard symbol None. Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Titanium dioxide	13463-67-7	10 - 30	
Kaolin, calcined	92704-41-1	1 - 5	
Zinc oxide	1314-13-2	0.5 - 1.5	
Cristobalite	14464-46-1	0.1 - 1	
Flux Calcined Diatomaceous Earth (DE)	68855-54-9	0.1 - 1	

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in

percent by volume.

The manufacturer has claimed the exact percentage as trade secret under the OSHA Hazard

Communication Standard.

BEHR® ULTRA Stain-Blocking Flat Ceiling Paint & Primer - Ultra Pure White Version #: 02 Revision date: 09-September-2020 Issue date: 05-February-2020 951900

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Most important Rinse mouth. Get medical attention if symptoms occur.

symptoms/effects, acute and delayed

Direct contact with eyes may cause temporary irritation.

Indication of immediate medical attention and special

treatment needed

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

Treat symptomatically.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

This product is miscible in water.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

Value

SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components **Type** Flux Calcined TWA 0.05 mg/m3

Diatomaceous Earth (DE) (CAS 68855-54-9)

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components **Type** Value **Form** Cristobalite (CAS PEL 0.05 mg/m3 Respirable dust. 14464-46-1)

BEHR® ULTRA Stain-Blocking Flat Ceiling Paint & Primer - Ultra Pure White 951900 Version #: 02 Revision date: 09-September-2020 Issue date: 05-February-2020

Components	Туре) Value	Form
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
Zinc oxide (CAS 1314-13-2)	PEL	5 mg/m3	Respirable fraction.
		5 mg/m3	Fume.
		15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFF Components	R 1910.1000) Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable.
		1.2 mppcf	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Components	Values Type	Value	Form
Cristobalite (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
7:no avido (CAC 1211 12 2)	STEL	10 mg/m3	Respirable fraction.
Zinc oxide (CAS 1314-13-2)			
Zinc oxide (CAS 1314-13-2)	TWA	2 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to		2 mg/m3	Respirable fraction.
, , , , , , , , , , , , , , , , , , ,		2 mg/m3 Value	Respirable fraction. Form
US. NIOSH: Pocket Guide to	Chemical Hazards	-	·
US. NIOSH: Pocket Guide to Components Cristobalite (CAS	Chemical Hazards Type	Value	Form
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1)	Chemical Hazards Type TWA	Value 0.05 mg/m3	Form Respirable dust.
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1)	Type TWA Ceiling	Value 0.05 mg/m3 15 mg/m3	Form Respirable dust. Dust.
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1)	TWA Ceiling STEL	Value 0.05 mg/m3 15 mg/m3 10 mg/m3	Form Respirable dust. Dust. Fume.
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1)	TWA Ceiling STEL	Value 0.05 mg/m3 15 mg/m3 10 mg/m3 5 mg/m3 5 mg/m3	Form Respirable dust. Dust. Fume. Dust.
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1) Zinc oxide (CAS 1314-13-2)	Type TWA Ceiling STEL TWA	Value 0.05 mg/m3 15 mg/m3 10 mg/m3 5 mg/m3 6 ingredient(s). Ventilation rates should be exhaust ventilation, or other added exposure limits. If exponential exposure limits and additional exposure limits.	Form Respirable dust. Dust. Fume. Dust. Fume. matched to conditions. If rengineering controls to
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1) Zinc oxide (CAS 1314-13-2) logical limit values propriate engineering trols	TWA Ceiling STEL TWA No biological exposure limits noted for the Good general ventilation should be used applicable, use process enclosures, local maintain airborne levels below recommer	Value 0.05 mg/m3 15 mg/m3 10 mg/m3 5 mg/m3 6 ingredient(s). Ventilation rates should be exhaust ventilation, or other acceptable level.	Form Respirable dust. Dust. Fume. Dust. Fume. matched to conditions. If rengineering controls to
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1) Zinc oxide (CAS 1314-13-2) logical limit values propriate engineering trols vidual protection measures, Eye/face protection Skin protection	TWA Ceiling STEL TWA No biological exposure limits noted for the Good general ventilation should be used applicable, use process enclosures, local maintain airborne levels below recommer established, maintain airborne levels to a such as personal protective equipment Wear safety glasses with side shields (or	Value 0.05 mg/m3 15 mg/m3 10 mg/m3 5 mg/m3 6 ingredient(s). Ventilation rates should be exhaust ventilation, or other orded exposure limits. If exponsion acceptable level.	Form Respirable dust. Dust. Fume. Dust. Fume. matched to conditions. If rengineering controls to
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1) Zinc oxide (CAS 1314-13-2) logical limit values propriate engineering trols vidual protection measures, Eye/face protection Skin protection Hand protection	TWA Ceiling STEL TWA No biological exposure limits noted for the Good general ventilation should be used applicable, use process enclosures, local maintain airborne levels below recommer established, maintain airborne levels to a such as personal protective equipment	Value 0.05 mg/m3 15 mg/m3 10 mg/m3 5 mg/m3 6 ingredient(s). Ventilation rates should be exhaust ventilation, or other orded exposure limits. If exponsion acceptable level.	Form Respirable dust. Dust. Fume. Dust. Fume. matched to conditions. If rengineering controls to
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1) Zinc oxide (CAS 1314-13-2) logical limit values propriate engineering trols vidual protection measures, Eye/face protection Skin protection Hand protection Skin protection	TWA Ceiling STEL TWA No biological exposure limits noted for the Good general ventilation should be used applicable, use process enclosures, local maintain airborne levels below recommer established, maintain airborne levels to a such as personal protective equipment Wear safety glasses with side shields (or Wear appropriate chemical resistant glov	Value 0.05 mg/m3 15 mg/m3 10 mg/m3 5 mg/m3 6 ingredient(s). Ventilation rates should be exhaust ventilation, or other orded exposure limits. If exponsion acceptable level.	Form Respirable dust. Dust. Fume. Dust. Fume. matched to conditions. If rengineering controls to
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1) Zinc oxide (CAS 1314-13-2) logical limit values propriate engineering trols vidual protection measures, Eye/face protection Skin protection Hand protection Skin protection Other	TWA Ceiling STEL TWA No biological exposure limits noted for the Good general ventilation should be used applicable, use process enclosures, local maintain airborne levels below recommer established, maintain airborne levels to a such as personal protective equipment Wear safety glasses with side shields (or Wear appropriate chemical resistant glov Wear suitable protective clothing.	Value 0.05 mg/m3 15 mg/m3 10 mg/m3 5 mg/m3 e ingredient(s). Ventilation rates should be exhaust ventilation, or other acceptable level. goggles).	Form Respirable dust. Dust. Fume. Dust. Fume. matched to conditions. If r engineering controls to osure limits have not been
US. NIOSH: Pocket Guide to Components Cristobalite (CAS 14464-46-1) Zinc oxide (CAS 1314-13-2) logical limit values propriate engineering trols vidual protection measures, Eye/face protection Skin protection Hand protection Skin protection	TWA Ceiling STEL TWA No biological exposure limits noted for the Good general ventilation should be used applicable, use process enclosures, local maintain airborne levels below recommer established, maintain airborne levels to a such as personal protective equipment Wear safety glasses with side shields (or Wear appropriate chemical resistant glov	Value 0.05 mg/m3 15 mg/m3 10 mg/m3 5 mg/m3 6 ingredient(s). Ventilation rates should be exhaust ventilation, or other acceptable level. goggles). goggles). es.	Form Respirable dust. Dust. Fume. Dust. Fume. matched to conditions. If r engineering controls to be

SDS US

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color White.
Odor Slight.

Odor threshold Not available.

pH 7 - 10

Melting point/freezing point Not available.

Initial boiling point and boiling > 99 °F (> 37.2 °C)

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit laws N

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Vapor pressureNot available.Vapor densityNot available.

Relative density 1.43

Solubility(ies)

Solubility (water) Soluble.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 50 - 140 KU at 25°C

Other information

Density11.91 lbs/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

VOC 14 g/l (including water) (Material)

29 g/l (excluding water) (Coating)

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged skin contact may cause temporary irritation.

BEHR® ULTRA Stain-Blocking Flat Ceiling Paint & Primer - Ultra Pure White
951900 Version #: 02 Revision date: 09-September-2020 Issue date: 05-February-2020

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components Species Test Results

Titanium dioxide (CAS 13463-67-7)

Acute Oral

LD50 Rat > 5000 mg/kg

Zinc oxide (CAS 1314-13-2)

Acute Oral

LD50 Rat > 5 g/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

CarcinogenicityDue to the form of the product, exposure to the potentially carcinogenic components is not

expected.

IARC Monographs. Overall Evaluation of Carcinogenicity

Cristobalite (CAS 14464-46-1) 1 Carcinogenic to humans.

Titanium dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

NTP Report on Carcinogens

Cristobalite (CAS 14464-46-1) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Cristobalite (CAS 14464-46-1)

Cancer
Flux Calcined Diatomaceous Earth (DE)

Cancer

(CAS 68855-54-9)

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure

Not classified.

Specific target organ toxicity -

Not classified.

repeated exposure

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil This product is water soluble and may disperse in soil.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

BEHR® ULTRA Stain-Blocking Flat Ceiling Paint & Primer - Ultra Pure White

951900 Version #: 02 Revision date: 09-September-2020 Issue date: 05-February-2020

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the Disposal instructions

material under controlled conditions in an approved incinerator.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Zinc oxide (CAS 1314-13-2)

Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Cristobalite (CAS 14464-46-1) Cancer Flux Calcined Diatomaceous Earth (DE) Cancer

(CAS 68855-54-9)

Cristobalite (CAS 14464-46-1) lung effects Flux Calcined Diatomaceous Earth (DE) lung effects

(CAS 68855-54-9)

Cristobalite (CAS 14464-46-1) immune system effects Flux Calcined Diatomaceous Earth (DE) immune system effects

(CAS 68855-54-9)

Cristobalite (CAS 14464-46-1) kidney effects Flux Calcined Diatomaceous Earth (DE) kidnev effects

(CAS 68855-54-9)

Toxic Substances Control Act (TSCA) All components are listed on or exempt from the U.S. EPA TSCA Inventory

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name CAS number % by wt. Zinc oxide 1314-13-2 0.5 - 1.5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

BEHR® ULTRA Stain-Blocking Flat Ceiling Paint & Primer - Ultra Pure White 951900 Version #: 02 Revision date: 09-September-2020 Issue date: 05-February-2020

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act N

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Cristobalite (CAS 14464-46-1) Titanium dioxide (CAS 13463-67-7) Zinc oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

3-lodo-2-propynyl butylcarbamate (CAS 55406-53-6)

Cristobalite (CAS 14464-46-1) Titanium dioxide (CAS 13463-67-7) Zinc oxide (CAS 1314-13-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Cristobalite (CAS 14464-46-1)

Flux Calcined Diatomaceous Earth (DE) (CAS 68855-54-9)

Titanium dioxide (CAS 13463-67-7) Zinc oxide (CAS 1314-13-2)

US. Rhode Island RTK

Cristobalite (CAS 14464-46-1) Titanium dioxide (CAS 13463-67-7) Zinc oxide (CAS 1314-13-2)

16. Other information, including date of preparation or last revision

Issue date 05-February-2020 **Revision date** 09-September-2020

Version # 02

HMIS® ratings Health: 0

Flammability: 0 Physical hazard: 0

List of abbreviations Ceiling: Short Term Exposure Limit Ceiling value.

DOT: Department of Transportation (49 CFR 172.101).

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous

Chemicals in Bulk.

IMDG Code: International Maritime Dangerous Goods Code.

LC50: Lethal Concentration, 50%.

LD50: Lethal Dose, 50%.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PEL: Permissible Exposure Limit. STEL: Short-Term Exposure Limit. TWA: Time Weighted Average Value.

References HSDB® - Hazardous Substances Data Bank

IARC Monographs. Overall Evaluation of Carcinogenicity

DisclaimerBehr Process LLC cannot anticipate all conditions under which this information and its product, or

the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

BEHR® ULTRA Stain-Blocking Flat Ceiling Paint & Primer - Ultra Pure White

951900 Version #: 02 Revision date: 09-September-2020 Issue date: 05-February-2020 7 / 7