

**1. Product and company identification**

Product name	Sikaflex®-15 LM+
Supplier	Sika Corporation 201 Polito Avenue Lyndhurst, NJ 07071
Telephone	(201) 933-8800
Telefax	(201) 804-1076
Emergency telephone	CHEMTREC: 800-424-9300
e-mail address of person responsible for this SDS	INTERNATIONAL: 703-527-3887 ehs@sika-corp.com
Manufacturer	Sika Corporation, Operations 201 Polito Avenue Lyndhurst, NJ 07071 www.sikausa.com
Telephone	(201) 933 - 8800
Chemical family	Polyurethane

2. Hazards identification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Potential Health Effects

Inhalation	Harmful if inhaled in high concentrations
Skin	May cause allergic skin reaction.
Eyes	May cause eye irritation.
Ingestion	May cause gastrointestinal disturbance.
Warning	Causes central nervous system depression Possible cancer hazard. Contains material which may cause cancer based on animal data.

See Section 11 for more detailed information on health effects and symptoms.

3. Composition/information on ingredients

<u>Component</u>	<u>CAS Number</u>
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	68515-49-1
Isophoronedialdimine	932742-30-8
xylene	1330-20-7
ethylbenzene	100-41-4
quartz (SiO ₂)	14808-60-7



There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First aid measures

First aid procedures

Inhalation	If inhaled, remove to fresh air. If breathing is difficult, trained personnel should give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact	In case of contact, immediately flush skin with soap and plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately if symptoms occur.
Eye contact	If easy to do, remove contact lens, if worn. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.
Ingestion	If swallowed, contact a poison control center or physician immediately. Do NOT induce vomiting unless directed to do so by medical personnel Never give anything by mouth to an unconscious person.

Notes to physician

Treatment	No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
-----------	--

5. Fire-fighting measures

Fire fighting

Suitable extinguishing media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	none
Further information	Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk without suitable training.

Protective equipment and precautions for firefighters

Special protective equipment for firefighters	Firefighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
---	--



6. Accidental release measures

Personal precautions	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. No action shall be taken involving any personal risk without suitable training. Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray. Material can create slippery conditions.
Environmental precautions	Local authorities should be advised if significant spillages cannot be contained. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
Methods for containment and cleaning up	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Large spills should be collected mechanically (remove by pumping) for disposal.

7. Handling and storage

Handling	For personal protection see section 8. Avoid inhalation, ingestion and contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in properly labeled containers. To maintain product quality, do not store in heat or direct sunlight. Store in accordance with local regulations.

8. Exposure controls/personal protection

Exposure limit(s)

<u>Component</u>	<u>CAS Number</u>	<u>Content %</u>	<u>Basis *</u>	<u>Value</u>	<u>Exposure limit(s) / Form of exposure</u>
xylene	1330-20-7	1 - 5	ACGIH	TWA	100 ppm
		1 - 5	ACGIH	STEL	150 ppm
		1 - 5	OSHA P1	TWA	100 ppm 435 mg/m3
		1 - 5	OSHA P0	TWA	100 ppm 435 mg/m3
		1 - 5	OSHA P0	STEL	150 ppm 655 mg/m3



Material Safety Data Sheet

Sikaflex®-15 LM+

Revision Date 11/14/2012

Print Date 11/14/2012

ethylbenzene	100-41-4	0.1 - 1	ACGIH	TWA	100 ppm
		0.1 - 1	ACGIH	STEL	125 ppm
		0.1 - 1	OSHA P1	TWA	100 ppm 435 mg/m3
		0.1 - 1	OSHA P0	TWA	100 ppm 435 mg/m3
		0.1 - 1	OSHA P0	STEL	125 ppm 545 mg/m3

*** Basis**

ACGIH. Threshold Limit Values (TLV)

OSHA P0. Table Z-1, Limit for Air Contaminant (1989 Vacated Values)

OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant

OSHA P2. Permissible Exposure Limits (PEL), Table Z-2

OSHA Z3. Table Z-3, Mineral Dust

Engineering measures

Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Skin and body protection

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hygiene measures

Avoid contact with skin, eyes and clothing.
Handle in accordance with good industrial hygiene and safety practice.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.



9. Physical and chemical properties**Appearance**

Form	paste
Color	various
Odor	aromatic

Safety data

Flash point	Note: not applicable
Density	ca.1.36 g/cm ³ at 68 °F (20 °C)
Viscosity, kinematic	> 7 mm ² /s at 104 °F (40 °C)
Volatile organic compounds (VOC) content	32.7 g/l

10. Stability and reactivity

Stability	Stable under normal conditions.
Conditions to avoid	not applicable
Materials to avoid	not applicable
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological information

Chronic Exposure	Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels. Reports have associated repeated and prolonged exposure to some of the chemicals in this product with permanent brain,liver, kidney and nervous system damage. Intentional misuse by deliberate concentration and inhalation of vapors may be harmful or fatal.
------------------	--

Carcinogenicity

IARC	Group 1: Carcinogenic to humans quartz (SiO ₂) 14808-60-7 Group 2B: Possibly carcinogenic to humans ethylbenzene 100-41-4
OSHA	not applicable
NTP	not applicable
ACGIH	Suspected human carcinogen quartz (SiO ₂) 14808-60-7



Material Safety Data Sheet

Sikaflex®-15 LM+

Revision Date 11/14/2012

Print Date 11/14/2012

Confirmed animal carcinogen with unknown relevance to humans
ethylbenzene 100-41-4

12. Ecological information

Other information

Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

13. Disposal considerations

Waste disposal methods

Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

15. Regulatory information

Federal Regulations

TSCA Status

On TSCA Inventory

SARA 311/312 Hazards

Acute Health Hazard

Chronic Health Hazard

EPCRA - Emergency Planning Community Right - To - Know

SARA 302 Ingredients

not applicable

SARA 313 Ingredients

xylene

1330-20-7

1.7 %

Clean Air Act

Ozone-Depletion Potential

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

xylene

1330-20-7

1.7 %

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).



Material Safety Data Sheet

Sikaflex®-15 LM+

Revision Date 11/14/2012

Print Date 11/14/2012

State Regulations

California Prop. 65 Ingredients

WARNING! This product contains a chemical known in the State of California to cause cancer.


WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

16. Other information

HMIS Classification

Health	*	2
Flammability		0
Physical Hazard		0
Personal Protection		C

NFPA Classification



Caution: HMIS® ratings and NFPA ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® and NFPA ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® and NFPA ratings are to be used with a fully implemented HMIS® and NFPA program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). NFPA or the National Fire Protection Association is a private non-profit organization and an authoritative source of technical background, data, and consumer advice on fire protection, problems and prevention. Please note HMIS® attempts to convey full health warning information to all employees while NFPA is meant primarily for fire fighters and other emergency responders.

Notes to Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.



Material Safety Data Sheet

Sikaflex®-15 LM+

Revision Date 11/14/2012

Print Date 11/14/2012

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.